


## NPN Transistor



## ■ Features

- Low Cob. Cob=2.0pF (Typ.)
- Complementary to 2SA1576A

## ■ Simplified outline(SOT-323)

## ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V <sub>CBO</sub>	60	V
Collector - Emitter Voltage	V <sub>CEO</sub>	50	
Emitter - Base Voltage	V <sub>EBO</sub>	7	
Collector Current - Continuous	I <sub>c</sub>	150	mA
Collector Power Dissipation	P <sub>c</sub>	200	mW
Junction Temperature	T <sub>j</sub>	150	°C
Storage Temperature Range	T <sub>stg</sub>	-55 to 150	

## ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	V <sub>CBO</sub>	I <sub>c</sub> = 100 uA, I <sub>e</sub> = 0	60			V
Collector-emitter breakdown voltage	V <sub>CEO</sub>	I <sub>c</sub> = 1 mA, I <sub>b</sub> = 0	50			
Emitter-base breakdown voltage	V <sub>EBO</sub>	I <sub>e</sub> = 100 uA, I <sub>c</sub> = 0	7			
Collector-base cut-off current	I <sub>cbo</sub>	V <sub>CB</sub> = 60V, I <sub>e</sub> = 0			0.1	uA
Emitter cut-off current	I <sub>ebo</sub>	V <sub>EB</sub> = 7V, I <sub>c</sub> = 0			0.1	
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>c</sub> =50 mA, I <sub>b</sub> =5mA			0.4	V
Base-emitter saturation voltage	V <sub>BE(sat)</sub>	I <sub>c</sub> =50 mA, I <sub>b</sub> =5mA			1.2	
DC current gain	h <sub>FE</sub>	V <sub>CE</sub> = 6V, I <sub>c</sub> = 1mA	120		560	
Collector output capacitance	C <sub>ob</sub>	V <sub>CE</sub> = 12V, I <sub>e</sub> =0, f=1MHz		2	3.5	pF
Transition frequency	f <sub>T</sub>	V <sub>CE</sub> = 12V, I <sub>e</sub> =-2mA, f=100 MHz		180		MHz

■ Classification of h<sub>FE</sub>

Type	2SC4081-Q	2SC4081-R	2SC4081-S
Range	120-270	180-390	270-560
Marking	BQ	BR	BS

## ■ Typical Characteristics




Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics ( $I_c$ )




Fig.3 Grounded emitter output characteristics ( $I_c$ )




Fig.4 DC current gain vs. collector current ( $H_{FE}$ )




Fig.5 DC current gain vs. collector current ( $H_{FE}$ )




Fig.6 Collector-emitter saturation voltage vs. collector current




Fig.7 Collector-emitter saturation voltage vs. collector current ( $V_{cesat}$ )




Fig.8 Collector-emitter saturation voltage vs. collector current ( $V_{cesat}$ )




Fig.9 Gain bandwidth product vs. emitter current


**■ Typical Characteristics**

Fig.10 Collector output capacitance vs.  
collector-base voltage  
Emitter input capacitance vs.  
emitter-base voltage





Fig.11 Base-collector time constant  
vs. emitter current

## ■ SOT-323



0 1 2 mm  
scale

DIMENSIONS (mm are the original dimensions)

UNIT	A	A <sub>1</sub> max	b <sub>p</sub>	c	D	E	e	e <sub>1</sub>	H <sub>E</sub>	L <sub>p</sub>	Q	v	w
mm	1.1 0.8	0.1	0.4 0.3	0.25 0.10	2.2 1.8	1.35 1.15	1.3	0.65	2.2 2.0	0.45 0.15	0.23 0.13	0.2	0.2